

NUDO®

A VERZATEC COMPANY



FRP SPRAY ADHESIVE

Ideal for Vertical Installation of the Following Materials
FRP • NRP • Plastic & Composite Wall Panels • Approved Sheet Vinyl

Spray-Lock FRP Spray Adhesive bonds approved wall and flooring material for commercial and residential vertical applications. Material must be structurally sound for use in commercial or residential applications. Spray-Lock FRP Spray Adhesive uses 60% less adhesive than traditional trowel-on adhesives. Spray-Lock FRP Spray Adhesive increases productivity with a faster application rate, saving time and money. It comes in an easy-to-use aerosol can.

- Cuts labor cost by about 30%
- 4-hour working time
- Apply directly to wall/instant grab
- Releasable for repositioning (prior to rolling)
- Adheres to porous and non-porous substrates
- 0.0 g/ml VOC content
- Water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- No offensive odors

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



SUITABLE SUBSTRATES

Spray-Lock FRP Spray Adhesive adheres to most smooth, clean surfaces, including properly prepared:

Plywood	Metal
Drywall	FRP
Water Resistant Drywall	Ceramic Tile
DensShield	

Note: Prime all joint compound.



COVERAGE GUIDE

FRP ADHESIVE | 22 oz AEROSOL CAN

70 ft² (6.5 m²)
Two 8 ft x 4 ft sheets

Shake aerosol can well. Snap black tab on top of trigger to activate the can. Aim at desired substrate. Pull black trigger to spray adhesive. Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to the Install Guide for detailed instructions. Note: Spray-Lock FRP Spray Adhesive must be installed and stored per the manufacturers recommendations or all warranties will be void.

TECHNICAL CHARACTERISTICS

Spray-Lock FRP Spray Adhesive formula is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock FRP Spray Adhesive is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B. Spray-Lock FRP Spray Adhesive uses non-ozone depleting HFC propellant.

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	4 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.0 g/ml calculated per EPA Test Method 8260B
STORAGE	Do not subject to freezing temperatures
CLIMATE-CONTROL SETTINGS	Building owners should become aware of the wall and flooring material manufacturer's guidelines for climate-control settings (temperature and humidity). These conditions must be monitored and kept constant to ensure the overall performance and long-term success of the installation.

Scan to learn more about Spray-Lock



NUDO[®]
A VERZATEC COMPANY

1500 Taylor Avenue
Springfield, IL 62703
www.Nudo.com

Ph: 800.826.4132
Fax: 217.528.8722