

Lightweight & Rigid Transportation Wall, Ceiling, and Flooring Panel



Nudo NuComb-A™ Transportation Panel 2 Year Limited Warranty

Limited Warranty: NuComb-A™ Transportation panels (“Panels”) manufactured by Nudo Products, Inc., 1500 Taylor Avenue, Springfield, IL 62703 are warranted for a period of Two (2) years from the date of purchase to be free from substantial defects in material and workmanship. This warranty is extended only to the original purchaser from authorized dealers and/or distributors and is non-transferable and subject to the terms, requirements and limitations provided in this limited warranty.

Compliance with Building Codes: Each purchaser of Panels is solely responsible for determining the effectiveness, suitability and safety of any particular application or use of the product. Because building code regulations vary from area to area, each Panel purchaser should consult local building and safety codes for specific requirements in connection with the use and installation of Panels.

Prior to Installation: Carefully inspect all Nudo panels. If panels are defective, notify Nudo Customer Service at 800.826.4132. Failure to do so shall be at the sole risk of the installer. Panel should be checked for excessive dents, scratches, telegraphing core materials, and delamination. Due to materials and lamination process panels may also vary in color, consistency, and tone. These variations are not to be considered defects. Make sure that all exposed edges and penetrations are sealed with silicone sealant. The installer must determine that the environmental conditions meet or exceeds all requirements specified in the installation guidelines. Before installing, remove packaging materials, but Do Not Remove the protective sheet on face of panels (When Applicable). Allow the panels to acclimate to the room temperature and humidity for at least 48 hours before installing. Acclimation temperature range should be 60° to 75°F (16°C to 24°) and relative humidity should be 35% to 55%. Ideally, the room temperature and humidity during acclimation and installation should be the same as the final operational conditions.

RESPONSIVENESS

CONSISTENCY

SOLUTIONS

Limited Warranty Coverage: Panels covered under this warranty are warranted for a period of Two (2) years from date of purchase to:

1. Be free from substantial defects in material and workmanship.
2. Not rot, rust, corrode, develop structural surface cracks, or require painting or refinishing.
3. Not delaminate due to materials when installed and used according to installation and use recommendations.

Condition of Warranty and Exclusions: Nudo Products, Inc. will at its option, upon documentation and verification of failure, repair or replace the panels, without charge, the above referenced product if it fails due to the above defects. This warranty does ***not cover*** or include labor costs or miscellaneous costs for removal and/or replacement.

This warranty applies only to panels stored, applied, installed and used in accordance with: (i) manufacturer's recommendations and technical bulletins; (ii) recognized standards of construction; and (iii) all building codes adopted by federal, state or local governments or agencies and applicable to the installation of the Panels.

*This warranty does **not cover**:*

1. Improper installation (non-conformance with the appropriate product installation guide, standards of construction, or governmental building codes.) Failure due to any adhesive, caulk or other accessories.
2. Damage (not resulting from defects) while in possession of the customer caused by improper storage, excessive moisture exposure, improper handling, improper installation, or other negligent causes.
3. Unreasonable use (including failure to provide reasonable and necessary maintenance), Normal pigmentation fading or abnormal fading due to exposure to ultraviolet rays. Damage or loss due to acts of God, improper storage, catastrophic events such as fire, hurricane, flooding.

Exclusion of Incidental and Consequential Damages: Nudo shall not be liable for any indirect, incidental, punitive, consequential, and exemplary or other damages of any kind; regardless of the legal theory used to allege such damages.

Claims:

To present a claim under this warranty, purchaser must send all information to the following within 30 days of failure and be accompanied by photographic evidence of material that has failed and original PO information.

Nudo Products, Inc.
Attn: Client Support
1500 Taylor Avenue
Springfield, IL. 62703

RESPONSIVENESS

CONSISTENCY

SOLUTIONS

DISCLAIMER OF EXPRESS AND IMPLIED WARRANTIES EXCEPT AS PROVIDED IN ASSOCIATED LIMITED WARRANTY: NUDO PRODUCTS, INC. ("NUDO") BELIEVES THAT THE INFORMATION PROVIDED IN THIS TECHNICAL DATA SHEET IS ACCURATE. NUDO MAKES NO REPRESENTATION, GUARANTEE, OR WARRANTY OF ANY KIND, NATURE, OR DESCRIPTION REGARDING THE ACCURACY OF ANY TECHNICAL DATA (INCLUDING, WITHOUT LIMITATION, REGARDING THE SUITABILITY, FIRE RESISTANCE, OR OTHER PHYSICAL PROPERTIES OF SUBSTRATE MATERIALS) PROVIDED BY SUBSTRATE MANUFACTURERS. ANY STATEMENT IN THIS TECHNICAL DATA SHEET REGARDING COMPLIANCE OR ADHERENCE TO ASTM TESTING STANDARDS IS BASED ON TESTING BY INDEPENDENT THIRD PARTIES, AND NUDO HAS NOT TESTED OR OTHERWISE VALIDATED THE SUBJECT PRODUCT'S COMPLIANCE WITH OR ADHERENCE TO ANY SUCH STANDARD. AS SUCH, NUDO OFFERS THIS INFORMATION IN GOOD FAITH, BUT WITHOUT ANY GUARANTEE OR WARRANTY EXCEPT AS SET FORTH IN THE EXPRESS LIMITED WARRANTY ASSOCIATED WITH THIS PRODUCT. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE DEEMED OR CONSTRUED TO CREATE ANY EXPRESS OR IMPLIED WARRANTY OF ANY KIND, NATURE OR DESCRIPTION, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN THE EVENT OF ANY CONFLICT BETWEEN THIS TECHNICAL DATA SHEET AND THE EXPRESS LIMITED WARRANTY ASSOCIATED WITH THIS PRODUCT, THE EXPRESS LIMITED WARRANTY SHALL CONTROL. BECAUSE CONDITIONS OF USE IN THE HANDS OF THE CUSTOMER OR OTHER END-USER ARE BEYOND NUDO'S CONTROL, THE CUSTOMER AND/OR END-USER ASSUMES ALL RISKS. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSIDERED TO RECOMMEND, SUPPORT, OR OTHERWISE ENDORSE ANY USE OF THIS PRODUCT THAT INFRINGES ON ANY VALID PATENT OR TO EXTEND ANY LICENSE UNDER ANY VALID PATENT OR PERMIT.

